

Product name

EUROCOLOR FLEX PLUS



Name and address of the producer

Fixcer Products, S.A.
 Ctra. Sant Cugat, Km 3
 08290 Cerdanyola del Vallès (Barcelona)
 Telf. 93 580 20 00 Fax 93 580 15 51

Factory: Avda. Gaudí, 15 – Pol. Ind. Rubí Sur – 08191 Rubí (Barcelona)

Product description

Product type: cementitious mortar for sealing

Identification: CG2 W Ar

Intended end use: mortar for sealing joints of 0 to 16 mm. thickness. Bright and permanent colours. Ideal for swimming pools, marble, terracotta, stoneware, glass mosaic, ceramic, natural stones,...

<p>CE Year: 05</p>	<p>N° of European Standard: EN 13.888 Adhesive type: cementitious mortar for sealing Intended end use: sealing joints from 0 to 16 mm, for internal and external uses, on floorings and wall.</p>	
<p>Name and address of the producer:</p> <p style="text-align: center;">FIXCER PRODUCTS, S.A. Ctra. Sant Cugat, Km 3 08290 Cerdanyola del Vallés (Barcelona)</p>		
Characteristics	Results	N° of test norm
Resistance to abrasion	Type CG2 W Ar EN 13888	EN 12808-2
Flexural strenght s.c.	Type CG2 W Ar EN 13888	EN 12808-3
Flexural strenght after freeze-thaw	Type CG2 W Ar EN 13888	EN 12808-3
Compressive strength s.c.	Type CG2 W Ar EN 13888	EN 12808-3
Compressive strength after freeze-thaw	Type CG2 W Ar EN 13888	EN 12808-3
Shrinkage	Type CG2 W Ar EN 13888	EN 12808-4
Water absorption after 30 m.	Type CG2 W Ar EN 13888	EN 12808-5
Water absorption after 4 h.	Type CG2 W Ar EN 13888	EN 12808-5

Final performances

Resistance to abrasion:

$\leq 1.000 \text{ mm}^3$, EN 12.808-2

Flexural strenght stored in a dry conditions:

$\geq 3,5 \text{ N/mm}^2$, EN 12.808-3

Flexural strenght after freeze-thaw:

$\geq 3,5 \text{ N/mm}^2$, EN 12.808-3

Compressive strenght stored in a dry conditions:

$\geq 15 \text{ N/mm}^2$, EN 12.808-3

Compressive strenght after freeze-thaw:

$\geq 15 \text{ N/mm}^2$, EN 12.808-3

Shrinkage:

$\leq 2 \text{ mm/m}$, EN 12.808-4

Water absorption after 30 min.:

$\leq 2 \text{ g}$. EN 12.808-5

Water absorption after 4 hours:

$\leq 5 \text{ g}$. EN 12.808-5

A handwritten signature in black ink, appearing to read 'Jordi Coloma', is written over a horizontal line. The signature is stylized and somewhat abstract.

JORDI COLOMA
Gerente
FIXCER PRODUCTS, S.A.