

# FIX-OIL

**Colourless treatment with an oil and water repellency effect for ceramic, stoneware, marble, granite...**



**CAUTION:**

**FIX-OIL** should not be used:

- ◆ At temperatures below +5 °C.
- ◆ For natural porcelain stoneware
- ◆ Modifying the formula.
- ◆ In cisterns or areas where water is stored.

**CONSUMPTION:**

According to the absorption of the surface: approx.: 0.15-0.18 lt./m<sup>2</sup>

**FIELDS OF APPLICATION**

- ◆ Clay, un-glazed ceramic tiles, stoneware, natural stones, marble, granite, manual terracotta, mechanical ceramic tiles, cotto...
- ◆ Repels grease, water and dirt stains... ideal for barbecues, kitchens, terraces, dining rooms...
- ◆ Can be used INDOORS and OUTDOORS.

**TECHNICAL CHARACTERISTICS**

**FIX-OIL** is a colourless mixture of polymers of a siloxanic base that waterproof and provides grease repellent properties to conveniently treated surfaces. The water and grease repellent effects reduce superficial absorption enabling the cleansing of stains. **FIX-OIL** does not modify the texture or the colour of the original piece.

**STORAGE**

In the original packaging, well closed and stored in covered and well-ventilated areas: 12 months. Do not expose to cold temperatures.

**PACKAGING**

**FIX-OIL** is available in the following formats: 1 lt. and 5 lt.

INDOOR AND OUTDOOR CLAY CERAMIC:				1 <sup>a</sup> layer		2 <sup>a</sup> layer (recommended)	
Clay	clay glued with mortar and after 40-50 days clay glued with cement and after 15-20days	Wash with GRESNET 25l/100sqm diluted in 1:5 water	rinse with water	winter: after 8-10 days summer: after 5-6 days	FIX-OIL 10-12lt./100sqm	after 24 h.	FIX-OIL 5-6lt./100sqm
UN-GLAZED NATURAL STONWARE FOR INDOOR AN OUTDOOR USE:				1 <sup>a</sup> layer		2 <sup>a</sup> layer (recommended)	
Un-glazed natural stoneware	After 7 days	Wash with GRESNET 25l/100sqm dilute 1:5 water	rinse with water	After 2 days	FIX-OIL 10-12lt./100sqm	after 24 h.	FIX-OIL 5-6lt./100sqm
NATURAL STONES, GRANITE, MARBLE INDOOR AND OUTDOOR:				1 <sup>a</sup> layer		2 <sup>a</sup> layer (recommended)	
Marble, granite or stone	wash with	FIX-SABO	rinse with water	let dry	FIX-OIL polished marble: 7-8lt./100sqm stone: 9-10lt./100sqm	after 24 h.	FIX-OIL polished marble: 3-4lt./100sqm stone: 5lt./100sqm

(does not alter the colour nor texture of the treated piece / apply with soft roller)

