

Product name

FIX-REVOCO



Name and address of the producer

Fixcer Products, S.A.
 Ctra. Sant Cugat, Km 3
 08290 Cerdanyola del Vallès (Barcelona)
 Telf. 93 580 20 00 Fax 93 580 15 51

Factory: Avda. Gaudí, 15 – Pol. Ind. Rubí Sur – 08191 Rubí (Barcelona)

Product description

Product type: rendering/plastering mortar for external (rendering) and internal (plastering) use.

Identification: GP – CS IV – W 2 waterproof

Intended end use: rendering/plastering mortar based on inorganic binders for external (rendering) and internal (plastering) use on walls, swimming pools, façades,...

| | | |
|--|--|------------------------|
| <p>CE Year: 06</p> | <p>Nº of European Standard: EN 998-1 Product type: part 1: specification for mortar for masonry. Intended end use: rendering/plastering mortar based on inorganic binders for external (rendering) and internal (plastering) use.</p> | |
| <p>Name and address of the producer: FIXCER PRODUCTS, S.A. Ctra. Sant Cugat, Km 3 08290 Cerdanyola del Vallés (Barcelona)</p> | | |
| Characteristics | Results (minimum) | Nº of test norm |
| Definition: | Mortar for usual uses: Type GP EN 998-1 | ----- |
| Fire resistance: | Mortar with <1% organic matter Type A1 EN 998-1 | EN 13501-1 |
| Water absorption: | Capillarity absorption Type W2 EN 998-1 | EN 1015-18 |
| Adhesion: | Adhesion on concrete and/or brick and type of rupture: Result declared according to EN 998-1 | EN 1015-12 |
| Mechanical resistances: | Resistance to compression: Type CS IV EN 998-1 | EN 1015-11 |

Final performances

Fire resistance:

Type A1 , according to EN 13501-1

Water capillarity absorption:

$C = 0,03 \text{ Kg/m}^2 \cdot \text{min}^{0,5} \ll 0,2 \Rightarrow$ type W2 according to
EN 1015-18

Adhesion:

Adhesion on concrete base:

$\geq 0,51 \text{ N/mm}^2$, and rupture between base and mortar (type A)
according to EN 1015-12

Adhesion on brick:

$\geq 0,39 \text{ N/mm}^2$, and rupture between base and mortar (type A)
according to EN 1015-12

Resistance to compression:

$\geq 12,7 \text{ N/mm}^2$, according to EN 1015-11

A handwritten signature in black ink, appearing to read 'Jordi Coloma', is written over a horizontal line. The signature is stylized and somewhat abstract.

JORDI COLOMA
Gerente
FIXCER PRODUCTS, S.A.