

EC DECLARATION OF CONFORMITY

**Product name**

**FIXMARMOL**



**Name and address of the producer**

Fixcer Products, S.A.  
 Ctra. Sant Cugat, Km 3  
 08290 Cerdanyola del Vallès (Barcelona)  
 Telf. 93 580 20 00 Fax 93 580 15 51

Factory: Avda. Gaudí, 15 – Pol. Ind. Rubí Sur – 08191 Rubí (Barcelona)

**Product description**

Product type: cementitious adhesive.

Identification: C2FT

Intended end use: highly adhesive flexible glue cement for attaching natural stones. Ideal for exteriors, façades and on supports of deformable media.

<p><b>CE</b> Year: 06</p>	<p><b>Nº of European Standard:</b> EN 12.004  <b>Adhesive type:</b> cementitious adhesive  <b>Intended end use:</b> product for tiling internal and external floorings or wall finishes.</p>	
<p><b>Name and address of the producer:</b></p> <p style="text-align: center;">FIXCER PRODUCTS, S.A.                  Ctra. Sant Cugat, Km 3                  08290 Cerdanyola del Vallés                  (Barcelona)</p>		
<b>Characteristics</b>	<b>Results</b>	<b>Nº of test norm</b>
<b>Bond strength</b>	- initial tensile adhesion strength: <b>Type C2 EN 12004</b>	EN 1348 section 8.2
<b>Durability</b>		
<b>Durability against climate/heat ageing action</b>	- tensile adhesion strength after heat ageing: <b>Type C2 EN 12004</b>	EN 1348 section 8.4
<b>Durability against water humidity action</b>	- tensile adhesion strength after water immersion: <b>Type C2 EN 12004</b>	EN 1348 section 8.3
<b>Durability against freeze/thaw cycles</b>	- tensile adhesion strength after freeze-thaw: <b>Type C2 EN 12004</b>	EN 1348 section 8.5

**Final performances**

Bond strength:

$\geq 0,5 \text{ N/mm}^2$ , 24 hours EN 1348 section 8.2

Tensile adhesion strength after heat ageing:

$\geq 1,0 \text{ N/mm}^2$ , EN 1348 section 8.4

Tensile adhesion strength after water immersion:

$\geq 1,0 \text{ N/mm}^2$ , EN 1348 section 8.3

Tensile adhesion strength after freeze-thaw:

$\geq 1,0 \text{ N/mm}^2$ , EN 1348 section 8.5

Tensile adhesion – open time:

$\geq 0,5 \text{ N/mm}^2$ , after 10 minutes EN 1346

Slip resistant:

$\leq 0,5 \text{ mm.}$ , EN 1308

A handwritten signature in black ink, appearing to read 'Jordi Coloma', is written over a horizontal line. The signature is stylized and includes a large, sweeping stroke that crosses the line.

JORDI COLOMA  
Gerente  
FIXCER PRODUCTS, S.A.