

**Product name**

**GROUT S-10**



**Name and address of the producer**

Fixcer Products, S.A.  
 Ctra. Sant Cugat, Km 3  
 08290 Cerdanyola del Vallès (Barcelona)  
 Telf. 93 580 20 00 Fax 93 580 15 51

Factory: Avda. Gaudí, 15 – Pol. Ind. Rubí Sur – 08191 Rubí (Barcelona)

**Product description**

Product type: mortar for securing and filling by pouring.

Identification: in accordance with attachment Z.A.2 based Conformity Verification System nº 4

Intended end use: ideal for use in filling under anchoring plates, anchoring railings or posts in concrete; can be used to seal fissures or cracks.

<p><b>CE</b> Year: 08</p>	<p><b>Nº of European Standard:</b> EN 1504-6  <b>Adhesive type:</b> mortar for securing and filling.  <b>Intended end use:</b> for use in filling under anchoring plates, anchoring railings or posts in concrete.</p>	
<p><b>Name and address of the producer:</b> FIXCER PRODUCTS, S.A.                  Ctra. Sant Cugat, Km 3                  08290 Cerdanyola del Vallés (Barcelona)</p>		
<b>Characteristics</b>	<b>Results</b>	<b>Nº of test norm</b>
<b>Tearing:</b>	<b>resists</b>	EN 1881
<b>Chloride content:</b>	<b>&lt; 0.05%</b>	EN 1015-17
<b>Reaction to fire:</b>	<b>A 1</b>	EN 13501-1
<b>Resistance to bending:</b>	<b>see results</b>	EN 1015-11
<b>Resistance to compression:</b>	<b>see results</b>	EN 12190

**Final performances**

Tearing:

0,003 mm <<< 0,6 mm maximum permitted  
a 123 KN >>> 75 KN minimum in accordance with EN 1881

Chloride content:

< 0,05% in accordance with EN 1015-17

Reaction to fire:

Type A 1 in accordance with EN 13501-1

Resistance to bending-compression:

$\geq 8,3 \text{ N/mm}^2$ , and  
 $\geq 54 \text{ N/mm}^2$ , respectively in accordance with EN 12190

A handwritten signature in black ink, appearing to read 'Jordi Coloma', is written over a horizontal line. The signature is stylized with large, sweeping strokes.

JORDI COLOMA  
Gerente  
FIXCER PRODUCTS, S.A.