

**Product name**

**JUNTATEC**



**Name and address of the producer**

Fixcer Products, S.A.  
 Ctra. Sant Cugat, Km 3  
 08290 Cerdanyola del Vallès (Barcelona)  
 Telf. 93 580 20 00 Fax 93 580 15 51

Factory: Avda. Gaudí, 15 – Pol. Ind. Rubí Sur – 08191 Rubí (Barcelona)

**Product description**

Product type: cementitious mortar for sealing

Identification: CG2 W Ar

Intended end use: mortar for sealing joints of 0 to 16 mm. Resistant to chemical aggression and very resistant to high temperatures. Ideal for SWIMMING POOLS.

<p><b>CE</b> Year: 07</p>	<p><b>Nº of European Standard:</b> EN 13.888  <b>Adhesive type:</b> cementitious mortar for sealing  <b>Intended end use:</b> sealing joints from 0 to 16 mm, for internal and external uses, on floorings and wall.</p>	
<p><b>Name and address of the producer:</b></p> <p style="text-align: center;">FIXCER PRODUCTS, S.A.                  Ctra. Sant Cugat, Km 3                  08290 Cerdanyola del Vallés                  (Barcelona)</p>		
<b>Characteristics</b>	<b>Results</b>	<b>Nº of test norm</b>
<b>Resistance to abrasion</b>	<b>Type CG2 W Ar EN 13888</b>	EN 12808-2
<b>Flexural strenght s.c.</b>	<b>Type CG2 W Ar EN 13888</b>	EN 12808-3
<b>Flexural strenght after freeze-thaw</b>	<b>Type CG2 W Ar EN 13888</b>	EN 12808-3
<b>Compressive strength s.c.</b>	<b>Type CG2 W Ar EN 13888</b>	EN 12808-3
<b>Compressive strength after freeze-thaw</b>	<b>Type CG2 W Ar EN 13888</b>	EN 12808-3
<b>Shrinkage</b>	<b>Type CG2 W Ar EN 13888</b>	EN 12808-4
<b>Water absorption after 30 m.</b>	<b>Type CG2 W Ar EN 13888</b>	EN 12808-5
<b>Water absorption after 4 h.</b>	<b>Type CG2 W Ar EN 13888</b>	EN 12808-5

**Final performances**

Resistance to abrasion:

$\leq 1.000 \text{ mm}^3$ , EN 12.808-2

Flexural strenght stored in a dry conditions:

$\geq 3,5 \text{ N/mm}^2$ , EN 12.808-3

Flexural strenght after freeze-thaw:

$\geq 3,5 \text{ N/mm}^2$ , EN 12.808-3

Compressive strenght stored in a dry conditions:

$\geq 15 \text{ N/mm}^2$ , EN 12.808-3

Compressive strenght after freeze-thaw:

$\geq 15 \text{ N/mm}^2$ , EN 12.808-3

Shrinkage:

$\leq 2 \text{ mm/m}$ , EN 12.808-4

Water absorption after 30 min.:

$\leq 2 \text{ g}$ . EN 12.808-5

Water absorption after 4 hours:

$\leq 5 \text{ g}$ . EN 12.808-5

A handwritten signature in black ink, appearing to read 'Jordi Coloma', is written over a horizontal line. The signature is stylized and somewhat abstract.

JORDI COLOMA  
Gerente  
FIXCER PRODUCTS, S.A.