

PLASTICAL

Filler for rendering and preparing gypsum or plasterboard walls for subsequent painting.



WARNING

PLASTICAL must not be used:

- ◆ On exteriors.
- ◆ On plasterboard facings subject to vibrations or impacts (use **PASTA PREPARADA**)
- ◆ For laying tiles (use **FIXAGRES FLEX YESO**)

FIELDS OF APPLICATION

- ◆ Repair, **rendering**, making good, filling, **smoothing**, spreading, touching-up, **levelling**, etc. - in short, any prior preparation of gypsum, plaster or plasterboard walls for subsequent painting or papering.
- ◆ Fills **cracks of gypsum** of up to 2 mm with no shrinkage or retraction.
- ◆ Ideal for **rendering ceilings** against gravity
- ◆ Ideal for repairing **plaster mouldings**.
- ◆ Also ideal for **fastening** electrical boxes and electrical corrugated pipes.

TECHNICAL CHARACTERISTICS

PLASTICAL is an advanced-formulation powder preparation. Mixing it with water produces a very creamy filler, easily worked with a spatula and ideal for smoothing fine layers on gypsum or plaster facings. Its outstanding technical features are:

- very easy to sand.
- quick-drying.
- for professional and DIY use.
- does not shrink, retract or crack.
- high yield.
- produces fine, very hard finishes.
- perfect final planimetry.



Ideal for filling small cracks.

DIRECTIONS FOR USE

- ◆ **Substrate:**
All substrates should always be resistant, solid and free of dust, wax, oils, grease, etc. They should also be perfectly hardened.
- ◆ **Preparing the mixture:**
Mix approximately 5 litres of water with each 10 kg of **PLASTICAL** until homogenous. Use an electric mixer at low r.p.m., although it can also be hand-mixed with a spatula. Leave to stand for 1 minute and remix. The mix is then ready to use.
- ◆ **Applying the mix:**
PLASTICAL is VERY easy to apply with a metal spatula. Apply it to a wall or ceiling, levelling and filling all cracks and holes. Apply sufficient pressure so that the product penetrates deeply.
- ◆ **Sanding the surface:**
Allow to dry for at least 30 minutes depending on the ambient temperature and humidity, and then sand carefully.



This process is very simple with **PLASTICAL**.

◆ **Final painting:**

The walls can normally be painted or papered the following day. **PLASTICAL** perfectly masks imperfections and produces an aesthetically excellent final result.



Fill and smooth all cracks and holes.



Leave to dry for at least 30 minutes.



With **PLASTICAL** the sanding process is VERY simple.

CONSUMPTION:	
PLASTICAL	1.8 kg for every 1000 cm ³

THECNICAL SPECIFICATIONS	FIXCER PLASTICAL
PRODUCT:	
• Type:	Preparation for repairing cracks and holes in gypsum, plaster or plasterboard walls.
• Density of the powder:	1.0 g/cm ³
• Granulometry:	ultra-fine.
• Toxicity:	Irritant, avoid contact with eyes and skin.
APPLICATION:	
• Mixing water:	5.0 litres / 10 kg pot
• Density of the mixture:	1.8 g/cm ³
• pH of the mix:	12.8
• Application temperature:	+ 5°C to + 35°C
• Usable for:	2-3 hours
• Paintable:	after 24 hours
• Fills cracks of up to:	2 mm.
FINAL PERFORMANCE:	
• Resistance to wear:	excellent
• Flexibility:	good
STORAGE:	
• In a dry, covered, ventilated place:	12 months
PRESENTATION:	
Supplied in:	1 kg and 10 kg in White