

4

# DECLARATION OF PERFORMANCE

### N° 039.01/13

### **Manufacturer:**

Fixcer Products, S.A. - Ctra. Sant Cugat, Km 3 - 08290 Cerdanyola del Vallès (Barcelona) Telf. 93 580 20 00 ; Fax 93 580 15 51 <u>Planta:</u> Avda. Gaudí, 15 - Pol. Ind. Rubí Sur - 08191 Rubí (Barcelona)

### **Identification code:**

Name:	EPOXICOLOR POOL
Product type:	SR-B1.5-AR0.3-IR14

# Intended use:

Self-levelling synthetic resin paste for indoor use

System of evaluation and verification of the constancy of performance:

### Harmonised standard:

EN 13813:2002

Notified body:

LGAI Technological Center, nº 0370

#### **Declared performance:**

Essential characteristics:	Performance	Technical specifications
Fire reaction	F	
Discharge of corrosive substances	SR	
Wear resistance	≤ AR1	EN 13813:2002
Tensile strength	≥ B1.5	
Impact resistance	≥ IR4	1

The performance of the previously identified product is in accordance with the declared performance.

This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer indicated above.

# Signed by and on behalf of the manufacturer by:

Inés Sánchez Directora Técnica

Cerdanyola del Vallès: 06-04-2021





# DECLARATION OF PERFORMANCE

### N° 039.02/13

### **Manufacturer:**

Fixcer Products, S.A. - Ctra. Sant Cugat, Km 3 - 08290 Cerdanyola del Vallès (Barcelona) Telf. 93 580 20 00 ; Fax 93 580 15 51 <u>Planta:</u> Avda. Gaudí, 15 - Pol. Ind. Rubí Sur - 08191 Rubí (Barcelona)

# **Identification code:**

Name:	EPOXICOLOR POOL
Product type:	C, PR (5/5.1)

# Intended use:

Coating for surface protection of concrete			
System of evaluation and verification of the constancy of performance:			
Harmonised standard:	EN 1504-2:2004		
Notified body:	LGAI Technological Center, nº 0370		

# **Declared performance:**

Essential characteristics:	Performance	Technical specifications		
Abrasion Resistance	< 3000 mg H22/1000 cycles/1000 g	EN 1504-2:2004		
Capillary absorption and water permeability	w < 0,1 kg/m <sup>2</sup> ·h <sup>0,5</sup>			
Impact resistance	Class III			
Adhesion by pull-off test	≥ 2,0 N/mm <sup>2</sup>			
Fire reaction	F			
Hazardous substances	View SDS			

The performance of the previously identified product is in accordance with the declared performance.

This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer indicated above.

\_\_\_\_

# Signed by and on behalf of the manufacturer by:

Inés Sánchez

Directora Técnica

Cerdanyola del Vallès: 06-04-2021