



DECLARATION OF PERFORMANCE

N° 020/13

Manufacturer:

Fixcer Products, S.A. - Ctra. Sant Cugat, Km 3 - 08290 Cerdanyola del Vallès (Barcelona)
Telf. 93 580 20 00 ; Fax 93 580 15 51
Planta: Avda. Gaudí, 15 – Pol. Ind. Rubí Sur – 08191 Rubí (Barcelona)

Identification code:

Name:	FIXARAPID FLEX
Product type:	C2FTS1

Intended use:

All indoor and outdoor installation

System of evaluation and verification of the constancy of performance:

3

Harmonised standard:

EN 12004:2007+A1:2012

Notified body:

LGAI Technological Center, nº 0370

Declared performance:

Essential characteristics:	Performance	Technical specifications
Fire reaction	A1	EN 12004:2007+A1:2012
Discharge of hazardous substances	View SDS	
Initial adhesion	$\geq 1,0 \text{ N/mm}^2$	
Early adhesion	$\geq 0,5 \text{ N/mm}^2$	
Adhesion after thermal ageing	$\geq 1,0 \text{ N/mm}^2$	
Adhesion after immersion in water	$\geq 1,0 \text{ N/mm}^2$	
Adhesion after freeze-thaw cycles	$\geq 1,0 \text{ N/mm}^2$	

The performance of the previously identified product is in accordance with the declared performance.

This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer indicated above.

Signed by and on behalf of the manufacturer by:

Inés Sánchez
Directora Técnica

Cerdanyola del Vallès: 06-04-2021

