(in accordance with Regulation (EU) 2020/878)

FIX-REPAR ANTI-OXID



Version 1 Date of compilation: 16/12/2015

Version 2 (replaces version 1) Revision date: 24/11/2023

Page 1 of 10 Print date: 24/11/2023

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: FIX-REPAR ANTI OXID Product Code: FRAN-3

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Not available.

1.3 Details of the supplier of the safety data sheet.

Company:	FIXCER PRODUCTS, S.A.U.
Address:	CTRA. SANT CUGAT KM. 3
City:	CERDANYOLA DEL VALLÈS
Province:	BARCELONA
Telephone:	93 586 20 03
Fax:	93 586 10 91
E-mail:	fixcer@fixcer.com
Web:	www.fixcer.com

1.4 Emergency telephone number: Servicio de Información Toxicológica (Instituto Nacional de Toxicología y Ciencias Forenses) Teléfono: +34 91 5620420. (Available 24 hours) Servicio de Información Toxicológica (Instituto Nacional de Toxicología y Ciencias Forenses) Teléfono: +34 91 5620420. Información en español (24h/365 días). Únicamente con la finalidad de proporcionar respuesta sanitaria en caso de urgencia.

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Eye Dam. 1 : Causes serious eye damage.

STOT SE 3 : May cause respiratory irritation. Skin Corr. 1 : Causes severe skin burns and eye damage. Skin Sens. 1 : May cause an allergic skin reaction.

2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008: Pictograms:



Signal Word:

Danger Hazard statemer

zard statements:	
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

Precautionary statements:

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

- P264 Wash ... thoroughly after handling. P280 Wear protective gloves/protective clo
 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

(in accordance with Regulation (EU) 2020/878)

FIX-REPAR ANTI-OXID



Version 1 Date of compilation: 16/12/2015 Version 2 (replaces version 1) Revision date: 24/11/2023 Page 2 of 10 Print date: 24/11/2023

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310Immediately call a POISON CENTER/doctor/...P321Specific treatment (see ... on this label).

Contains: Cement, portland, chemicals

2.3 Other hazards.

The mixture does not contain substances classified as PBT. The mixture does not contain substances classified as vPvB. The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

				(*)Classification - Regulation (EC) No 1272/2008	
	Identifiers	Name	Concentrate	Classification	Specifics concentration limits and Acute toxicity estimate
	CAS No: 65997-15-1 EC No: 266-043-4	[2] Cement, portland, chemicals	20 - 75 %	Eye Dam. 1, H318 - STOT SE 3, H335 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet. [2] Substance with a national workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

Contact with eyes may cause irreversible damage.

(in accordance with Regulation (EU) 2020/878)

FIX-REPAR ANTI-OXID



Version 1 Date of compilation: 16/12/2015

Version 2 (replaces version 1) Revision date: 24/11/2023

Page 3 of 10 Print date: 24/11/2023

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed.

Request immediate medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

SECTION 5: FIREFIGHTING MEASURES.

The product is NOT classified as flammable, in case of fire the following measures should be taken:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8. For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

(in accordance with Regulation (EU) 2020/878)

FIX-REPAR ANTI-OXID



Version 1 Date of compilation: 16/12/2015

Version 2 (replaces version 1) Revision date: 24/11/2023

Page 4 of 10 Print date: 24/11/2023

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and wellventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Cement, portland, chemicals 65997-15-1 España [1] Eight hours 4 (fracción respirable) United Kingdom [2] Short term 10 (inhalable dust) 4 (respirable dust) Éire [3] Eight hours 1 (Respirable fraction) Éire [3] Eight hours 1 (Respirable fraction) United States [4] (Cal/OSHA) Eight hours 5 (Respirable fraction) United States [5] (NIOSH) Eight hours 5 (Respirable fraction) Short term 10 (Total dust) 5 (Respirable fraction) Short term 10 (Total dust) 5 (Respirable fraction) United States [5] (NIOSH) Eight hours 5 (Respirable fraction) Inited States [5] (NIOSH) Eight hours 10 (Total dust) Short term 10 (Total dust) 5 (Respirable fraction) Short term 10 (Total dust) 5 (Respirable fraction) Inited States [5] (NIOSH) Eight hours 15 (Total dust) Short term 15 (Total dust) 5 (Respirable fraction) Inited States [6] (OSHA) Eight hours 15 (Total dust) Inited States [6] (OSHA) Eight hours 15 (Total dust) Inited States [6] (OSHA) Eight hours 10 (Total dust) Inited States [6] (OSHA) Eight hours 15 (Total dust) Inited States [6] (OS	Name	CAS No.	Country	Limit value	ppm	mg/m ³
Cement, portland, chemicals 65997-15-1 Eight hours 10 (inhalable dust) 4 (respirable dust) Gement, portland, chemicals 65997-15-1 Eight hours 1 (Respirable fraction) Short term 10 (Total dust) 5 (Respirable fraction) 5 (Respirable fraction) United States [4] (Cal/OSHA) Eight hours 10 (Total dust) United States [5] (NIOSH) Eight hours 10 (Total dust) Short term 10 (Total dust) 5 (Respirable fraction) United States [5] (NIOSH) Eight hours 10 (Total dust) Short term 10 (Total dust) 5 (Respirable fraction) 5 (Respirable fraction) United States [6] (OSHA) Eight hours 15 (Total dust) United States [6] (OSHA) Eight hours 15 (Total dust) United States [6] (OSHA) Eight hours 15 (Total dust) Short term 15 (Total dust) 5 (Respirable fraction) 5 (Respirable fraction) Short term 15 (Total dust) 5 (Respirable fraction) 5 (Respirable fraction) United States [6] (OSHA) Eight hours 15 (Total dust) United States [6] (OSHA) Eight hours 10 (Total dust) United States [6] (OSHA) Eight hours 15 (Total dust				Eight hours		
Cement, portland, chemicals 65997-15-1 Eight hours 10 (Total dust) 65997-15-1 65997-15-1 Eight hours 10 (Total dust) 65997-15-1 Eight hours 10 (Total dust) 5 (Respirable fraction) Short term 10 (Total dust) 5 (Respirable fraction) 5 (Respirable fraction) United States [5] (NIOSH) Eight hours 10 (Total dust) Short term 10 (Total dust) 5 (Respirable fraction) Short term 10 (Total dust) 5 (Respirable fraction) Short term 10 (Total dust) 5 (Respirable fraction) United States [5] (NIOSH) Eight hours 10 (Total dust) Short term 10 (Total dust) 5 (Respirable fraction) 5 (Respirable fraction) Short term 10 (Total dust) 5 (Respirable fraction) 5 (Respirable fraction) United States [6] (OSHA) Eight hours 15 (Total dust) United States [6] (OSHA) Eight hours 10 (Total dust) Counted by light-field techniques. Counted by light-field techniques. Counted by light-field techniques. Counted by light-field techniques. Counted by light-field techniques. Counted by light-field techniques.				Short term		
 Éire [3] Éight hours Short term United States [4] (Cal/OSHA) Eight hours Short term I0 (Total dust) 5 (Respirable fraction) Gight hours Short term United States [5] (NIOSH) Eight hours Short term I0 (Total dust) S(Respirable fraction) Short term I0 (Total dust) S(Respirable fraction) Short term I0 (Total dust) S(Respirable fraction) Short term In (Total dust) S(Respirable fraction) Short term In (Total dust) S(Respirable fraction) (In (In term) In (Total dust) S(Respirable fraction) (In (In term) In (In term)				Eight hours		dust) 4
Cement, portland, chemicals 65997-15-1 Eight hours 10 (Total dust) 5 (Respirable fraction) United States [4] (Cal/OSHA) Eight hours 10 (Total dust) 5 (Respirable fraction) United States [5] (NIOSH) Eight hours 10 (Total dust) 5 (Respirable fraction) United States [6] (OSHA) Eight hours 10 (Total dust) 5 (Respirable fraction) United States [6] (OSHA) Eight hours 15 (Total dust) 5 (Respirable fraction) Eight hours 15 (Total dust) 5 (Respirable fraction) 5 (Respirable fraction)				Short term		
Cement, portland, chemicals 65997-15-1 United States [5] (NIOSH) Eight hours 10 (Total dust) Short term 10 (Total dust) United States [5] (NIOSH) Fight hours 10 (Total dust) Short term 10 (Total dust) United States 5 (Respirable fraction) Short term 110 (Total dust) United States 5 (Respirable fraction) United States 110 (Total dust) [6] (OSHA) Fight hours Inited States [6] (OSHA) Eight hours 115 (Total dust) States 110 (Total dust)			Éire [3]	_		
Cement, portland, chemicals 65997-15-1 United States [4] (Cal/OSHA) United States [5] (NIOSH) Short term 10 (Total dust) Short term 5 (Respirable fraction) Short term 5 (Respirable fraction) Short term 10 (Total dust) Short term 5 (Respirable fraction) United States [5] (NIOSH) Image: Short term 15 (Total dust) Short term 5 (Respirable fraction) 50 (mppdf:Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques, Conversion fractors - mppdf X 35.3 = million particles per cubic meter = particles per cubic m				Short term		
Cement, portland, chemicals65997-15-1Short term10 (Total dust) 5 (Respirable fraction)65997-15-165997-15-1If (Total dust) Short term15 (Total dust) 5 (Respirable fraction)United States [6] (OSHA)United States [6] (OSHA)If (Total dust) 5 (Respirable fraction)15 (Total dust) 5 (Respirable fraction)United States [6] (OSHA)United States [6] (OSHA)If (Total dust) 5 (Respirable fraction)15 (Total dust) 5 (Respirable fraction)United States [6] (OSHA)If (Total dust) 5 (Respirable fraction)10 (Total dust) 5 (Respirable fraction)Image: Data states (10) (Total dust)Image: Data states (10) (Total dust)Image: Data states (10) (Image: Data states) (10) (Image: Data states)Image: Data states (10) (Image: Data states)Image: Data states (10) (Image: Data states)Image: Data states) (10) (Image: Data states)Image: Data states (10) (Image: Data states)Image: Data states)Image: Data states) (10) (Image: Data states)Image: Data states (10) (Image: Data states)Image: Data states)Image: Data states)Image: Data states (10) (Image: Data states)Image: Data states)Image: Data states)Image: Data states (10) (Image: Data states)Image: Data states)Image: Data states)Image: Data states (10) (Image: Data states)Image: Data states)Image: Data states)Image: Data states (10) (Image: Data states)Image: Data states)Image: Data states)Image: Data state states (10) (Image: Data state)Im				Eight hours		5 (Respirable
Cement, portland, chemicals 65997-15-1 Image: Second system of the system of				Short term		
Cement, portland, chemicals65997-15-1Short termImage: Comparison of the second				Eight hours		5 (Respirable
United States [6] (OSHA) United States [6] (OSHA) United States [6] (OSHA) United States [6] (OSHA) United States [6] (OSHA) Eight hours Seguetable (Conversion factors - mppcf X 35.3 = million particles per cubic meter = particles per cubic meter =				Short term		
Short term	Cement, portland, chemicals	65997-15-1		Eight hours		5 (Respirable fraction) 50 (mppcf:Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques. Conversion factors - mppcf X 35.3 = million particles per cubic meter = particles per
				Short term		

[1] Según la lista de Valores Límite Ambientales de Exposición Profesional adoptados por el Instituto Nacional de Seguridad y Salud en el Trabajo (INSST) para el año 2022.

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive.

[3] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

[4] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

(in accordance with Regulation (EU) 2020/878)

FIX-REPAR ANTI-OXID



Version 1 Date of compilation: 16/12/2015

Version 2 (replaces version 1) Revision date: 24/11/2023

Page 5 of 10 Print date: 24/11/2023

[5] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.
[6] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).
The product does NOT contain substances with Biological Limit Values.
8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Uses: PPE: Particle filter mask «CE» marking, category III. Made of filtering material, it covers nose, mouth and chin. CEN standards: EN 149 Maintenance: Should be replaced after use. Observations: South ever unless properly adjusted. Follow the manufacturer's instructions regarding suitable use of the equipment. Filter Type needed: P2 Hand protection: Protective gloves against chemicals. Characteristics: «CE» marking, category III. CEN standards: EN 374-1, En 374-2, EN 374-3, EN 420 Maintenance: Do on make any changes to the gloves that may after their resistance, or apply paints, solvents or adhesives. Observations: Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Material: PVC (polyvinyl chloride) Breakthrough time (min.): Material thickness (mm): Fye protection: PPE: Protective goggles with built-in frame. Material thickness (min.): 0,35 Eye protection: PPE: Protective goggles with built-in frame. Material bickness (min.): 0,35 Eye protection: PPE: Protective dothing, «CE» marking, category II. Protective clobing should not be too tight or loose in order not to obstruct the user's movements. <th>Concentration:</th> <th colspan="3">100 %</th>	Concentration:	100 %		
PPE: Particle filter mask Characteristics: «CE» marking, category III. Made of filtering material, it covers nose, mouth and chin. CEN standards: EN 149 Maintenance: Check for any tears, defects, etc. before use. Since it is disposable individual protection equipment, it should be replaced after use. Observations: Does not protect worker unless properly adjusted. Follow the manufacturer's instructions regarding suitable use of the equipment. Filter Type needed: P2 Hand protection: Protective gloves against chemicals. Characteristics: «CE» marking, category III. CEN standards: EN 374-1, En 374-2, EN 374-3, EN 420 Maintenance: Do on make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives. Observations: Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Alterial: PVC (polyvinyl chioride) Breakthrough time 480 Material thickness 0,35 PPE: Protective goggles with built-in frame. «CE» marking, category II. Eve protector with built-in frame for protection against dust, snoke, fog and vapour. CEN standards: EN 166, EN 167, EN 168 Maintenance: Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching				
Characteristics: CE* marking, category III. Made of filtering material, it covers nose, mouth and thin. Check for any tears, defects, etc. before use. Since it is disposable individual protection equipment, it should be replaced after use. Does not protect worker unless properly adjusted. Follow the manufacturer's instructions regarding suitable use of the equipment. Filter Type needed: P2 Hand protection: PFE: Protective gloves against chemicals. Characteristics: CE* marking, category III. CEN standards: EN 374-1, En 374-2, EN 374-3, EN 420 Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may after their resistance, or apply paints, solvents or adhesives. Observations: Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands. Material: PVC (polyvinyl chloride) Breakthrough time Material thickness 0,35 Eye protection: PFE: Protective goggles with built-in frame. < 	Breathing protection:			
Cladaderisus. chin. CEN standards: EN 149 Maintenance: Should be replaced after use. Observations: Does not protect worker unless properly adjusted. Follow the manufacturer's instructions regarding suitable use of the equipment. Filter Type needed: P2 Hand protection: Pretective gloves against chemicals. Characteristics: «CE» marking, category III. CEN standards: EN 374-1, En 374-2, EN 374-3, EN 420 Maintenance: Do not make any charges to the gloves that may after their resistance, or apply paints, solvents or adhesives. Observations: Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands. Material thickness 0,35 PPE: Protective goggles with built-in frame. Characteristics: «CE» marking, category III. Eve protector with built-in frame for protection against dust, smoke, fog and vapour. CEN standards: EN 165, EN 166, EN 167, EN 168 Maintenance: be disinfected periodically following the manufacturer's instructions. Observations: Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc. Skin protection: Protective cothing. CE» marking, catego	PPE:			
Maintenance: Check for any tears, defects, etc. before use. Since it is disposable individual protection equipment, it should be replaced after use. Observations: Does not protect worker unless properly adjusted. Follow the manufacturer's instructions regarding suitable use of the equipment. Filter Type needed: P2 Hand protection: Protective gloves against chemicals. Characteristics: «CE» marking, category III. CEN standards: EN 374-1, En 374-2, EN 374-3, EN 420 Maintenance: Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives. Observations: Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Alwarys use with clean, dry hands. Material thickness 0,35 Material: PVC (polyvinyl chloride) Breakthrough time or protection against dust, smoke, fog and vapour. CEN standards: EN 165, EN 166, EN 167, EN 168 Material scratching of the lenses, scraping etc. Scin protection: PPE: Protective clothing. Protective clothing. PPE: Protective disting category II. Protective clothing should hot be too tight or loose in order not to obstruct the user's movements. Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc. Skin protecti	Characteristics:			
Maintenance: should be replaced after use. Observations: Suitable use of the equipment. Filter Type needed: P2 Hand protection: Protective gloves against chemicals. PPE: Protective gloves against chemicals. Characteristics: «CE» marking, category III. CEN standards: EN 374-1, En 374-2, EN 374-3, EN 420 Maintenance: Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives. Observations: Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands. Material: PVC (polyvinyl chloride) Breakthrough time and (min.): 480 Material thickness 0,35 Eye protection: Protective goggles with built-in frame. (min.): > 480 Material thickness 0,35 CEN standards: EN 165, EN 166, EN 167, EN 168 Maintenance: Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Observations: Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc. Skin protection: Protective clothing. PPE: Protectiv	CEN standards:			
Observations: suitable use of the equipment. Filter Type needed: P2 Hand protection: PPE: PPE: Protective gloves against chemicals. CLN standards: EN 374-1, En 374-2, EN 374-3, EN 420 Maintenance: Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives. Observations: Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Material: PVC (polyvinyl chloride) Breakthrough time (min.): PFE: Protective goggles with built-in frame. Characteristics: «CE* marking, category III. Eye protector with built-in frame for protection against dust, smoke, fog and vapour. CEN standards: EN 165, EN 166, EN 167, EN 168 Maintenance: Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Observations: Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc. Skin protection: PPE: PPE: Protective clothing. Characteristics: order to ugarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.	Maintenance:	should be replaced after use.		
Hand protection: PPE: Protective gloves against chemicals. Characteristics: «CE» marking, category III. CEN standards: EN 374-1, En 374-2, EN 374-3, EN 420 Maintenance: Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives. Observations: Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Material: PVC (polyvinyl chloride) Breakthrough time (min.): PPE: Protective goggles with built-in frame. Material thickness (nm): CAracteristics: «CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour. CEN standards: EN 165, EN 166, EN 167, EN 168 Wisibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Observations: Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc. Stin protection: Protective clothing. Characteristics: CCs marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements. CDs standards: EN 374 PPE: Protective clothing.		suitable use of the equipment.		
PPE: Protective gloves against chemicals. Characteristics: «CE» marking, category III. CEN standards: EN 374-1, En 374-2, EN 374-3, EN 420 Maintenance: Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives. Observations: Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands. Material: PVC (polyvinyl chloride) Breakthrough time (mm): > 480 Material thickness (mm): PPE: Protective goggles with built-in frame. «CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour. Question (mm): CEN standards: EN 165, EN 167, EN 168 Waintenance: Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc. Skin protection: PPE: Protective clothing. PPE: Protective clothing. «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements. CEN standards: EN 340 In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. PPE: Work footwear. The protective clothing should offer a level of comfort in line with the level of prote		P2		
Characteristics: «CE» marking, category III. CEN standards: EN 374-1, En 374-2, EN 374-3, EN 420 Maintenance: Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives. Observations: Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands. Material: PVC (polyvinyl chloride) Breakthrough time resistance, or apply paints, solvents or adhesives. Characteristics: CE× marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour. Material thickness 0,35 CEN standards: EN 165, EN 166, EN 167, EN 168 Wisibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Observations is of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc. Skin protection: PPE: Protective clothing. Characteristics: GC× marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements. CEN standards: EN 340 Maintenance: In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. CEN standards: EN 340 In or				
Maintenance: Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives. Observations: Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands. Material: PVC (polyvinyl chloride) Breakthrough time (min.): > 480 Material thickness (mm): 0,35 Eye protection: Protective goggles with built-in frame. (mm): 0,35 Characteristics: CE* marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour. (mm): (mm): (mm): CEN standards: EN 165, EN 166, EN 167, EN 168 (sinifected periodically following the manufacturer's instructions. (bedisinfected periodically following the manufacturer's instructions. Observations: Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc. Skin protection: PPE: Protective clothing. PPE: Protective clothing. CEN standards: EN 340 In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions				
Maintenance: Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives. Observations: Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Material: PVC (polyvinyl chloride) Breakthrough time (min.): > 480 Material thickness (mm): 0,35 Eye protection: PPE: Protective goggles with built-in frame. (min.): > 480 Material thickness (mm): 0,35 Characteristics: CCE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour. CEN standards: EN 165, EN 166, EN 167, EN 168 Maintenance: Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Observations: Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc. Skin protection: PPE: Protective clothing. CEN standards: EN 340 In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. Maintenance: In order to guarantee uniform protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. Observations: terms of the hazard against whic	CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Observations: Always use with clean, dry hands. Material: PVC (polyvinyl chloride) Breakthrough time (min.): Material thickness (mm): PPE: Protective goggles with built-in frame. (CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour. CEN standards: EN 165, EN 166, EN 167, EN 168 Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Observations: Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc. Skin protection: PPE: PPE: Protective clothing. CEN standards: EN 340 Maintenance: CE* marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements. CEN standards: EN 340 Maintenance: In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. Observations: Every of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Work footwear. CEN standards: EN ISO 13287, EN 20347 This product adapts to the first	Maintenance:	Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or		
Protection: Protection: PPE: Protective goggles with built-in frame. Characteristics: «CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour. CEN standards: EN 165, EN 166, EN 167, EN 168 Maintenance: Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Observations: Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc. Skin protection: PPE: PPE: Protective clothing. CEN standards: EN 340 Maintenance: worder not to obstruct the user's movements. CEN standards: EN 340 Maintenance: In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Work footwear. Characteristics: CCE> marking, category II. CEN standards: EN ISO 13287, EN 20347 This product adapts to the first us	Observations:	Always use with clean, dry hands.		
PPE: Protective goggles with built-in frame. Characteristics: «CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour. CEN standards: EN 165, EN 166, EN 167, EN 168 Maintenance: Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Observations: Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc. Skin protection: Protective clothing. CR standards: EN 340 Reiner of to obstruct the user's movements. CEN standards: EN 340 Maintenance: In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Work footwear. Characteristics: «CE» marking, category II. CEN standards: EN 180 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.	Material:			
Characteristics: «CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour. CEN standards: EN 165, EN 166, EN 167, EN 168 Maintenance: Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Observations: Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc. Skin protection: Protective clothing. CR-s standards: EN 340 Maintenance: In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. Maintenance: The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Work footwear. Characteristics: «CE» marking, category II. CEN standards: EN 150 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. Work footwear: This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.	Eye protection:			
Characteristics: dust, smoke, fog and vapour. CEN standards: EN 165, EN 166, EN 167, EN 168 Maintenance: Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Observations: Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc. Skin protection: Protective clothing. Characteristics: CCE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements. CEN standards: EN 340 Maintenance: In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. Observations: The protective clothing should offer a level of comfort in line with the level of protection provided in of activity and the expected time of use. PPE: Work footwear. Characteristics: «CE» marking, category II. CEN standards: EN 150 13287, EN 20347 Maintenance: This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. Observations: CEN standards: EN 150 13287, EN 20347 Maintenance: This product adapts to the first user's foot shape. That is why, as well as for	PPE:			
Maintenance:Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.Skin protection:Protective clothing. (Characteristics:Protective clothing. (CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.CEN standards:EN 340 In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.PPE:Work footwear. Characteristics: (CE» marking, category II. CEN standards:PPE:Work footwear. Characteristics: (Characteristics: (CE» marking, category II. CEN standards: EN ISO 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.Observations:Censentiance: This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.	Characteristics:	dust, smoke, fog and vapour.		
Maintenance: be disinfected periodically following the manufacturer's instructions. Observations: Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc. Skin protection: PPE: PPE: Protective clothing. Characteristics: «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements. CEN standards: EN 340 Maintenance: In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Work footwear. Characteristics: «CE» marking, category II. CEN standards: EN ISO 13287, EN 20347 Maintenance: This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. Observations: Work footwear for professional use includes protection elements aimed at protecting users against any	CEN standards:			
Observations: scraping etc. Skin protection: PPE: PPE: Protective clothing. Characteristics: «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements. CEN standards: EN 340 Maintenance: In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. Observations: The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Work footwear. Characteristics: «CE» marking, category II. CEN standards: EN ISO 13287, EN 20347 Maintenance: This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. Observations: Work footwear for professional use includes protection elements aimed at protecting users against any	Maintenance:			
PPE: Protective clothing. Characteristics: «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements. CEN standards: EN 340 Maintenance: In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. Observations: The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Work footwear. Characteristics: «CE» marking, category II. CEN standards: EN ISO 13287, EN 20347 Maintenance: This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. Observations: Work footwear for professional use includes protection elements aimed at protecting users against any	Observations:			
Characteristics:«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.CEN standards:EN 340Maintenance:In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.PPE:Work footwear. Characteristics: Resonance:PPE:Work footwear. Characteristics: Maintenance:Maintenance:This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. Work footwear for professional use includes protection elements aimed at protecting users against any				
Characteristics.order not to obstruct the user's movements.CEN standards:EN 340Maintenance:In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.PPE:Work footwear. Characteristics: CEN standards:CEN standards:EN ISO 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.Observations:Work footwear for professional use includes protection elements aimed at protecting users against any	PPE:			
CEN standards:EN 340Maintenance:In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.PPE:Work footwear.Characteristics:«CE» marking, category II.CEN standards:EN ISO 13287, EN 20347Maintenance:This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. Work footwear for professional use includes protection elements aimed at protecting users against any	Characteristics:			
Maintenance:In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.PPE:Work footwear. Characteristics: CEN standards:Work footwear. EN ISO 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. Work footwear for professional use includes protection elements aimed at protecting users against any	CEN standards:			
Observations: The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Work footwear. Characteristics: «CE» marking, category II. CEN standards: EN ISO 13287, EN 20347 Maintenance: This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. Observations: Work footwear for professional use includes protection elements aimed at protecting users against any		In order to guarantee uniform protection, follow the washing and maintenance instructions provided by		
PPE: Work footwear. Characteristics: «CE» marking, category II. CEN standards: EN ISO 13287, EN 20347 Maintenance: This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. Observations: Work footwear for professional use includes protection elements aimed at protecting users against any	Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level		
Characteristics: «CE» marking, category II. CEN standards: EN ISO 13287, EN 20347 Maintenance: This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. Observations: Work footwear for professional use includes protection elements aimed at protecting users against any	PPE:			
Maintenance: This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. Work footwear for professional use includes protection elements aimed at protecting users against any	Characteristics:	«CE» marking, category II.		
Observations: Work footwear for professional use includes protection elements aimed at protecting users against any		This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should		
	Observations:			

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

(in accordance with Regulation (EU) 2020/878)

FIX-REPAR ANTI-OXID



Version 1 Date of compilation: 16/12/2015 Version 2 (replaces version 1) Revision date: 24/11/2023 Page 6 of 10 Print date: 24/11/2023

9.1 Information on basic physical and chemical properties.

Physical state: Solid - Dust

Colour: Not applicable/Not available due to the nature/properties of the product Odour: Not applicable/Not available due to the nature/properties of the product Odour threshold: Not applicable/Not available due to the nature/properties of the product Melting point: >1000 °C Freezing point: Not applicable/Not available due to the nature/properties of the product Boiling point or initial boiling point and boiling range: Not applicable/Not available due to the nature/properties of the product Flammability: Not applicable/Not available due to the nature/properties of the product Lower explosion limit: Not applicable/Not available due to the nature/properties of the product Upper explosion limit: Not applicable/Not available due to the nature/properties of the product Flash point: Not applicable/Not available due to the nature/properties of the product Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product Decomposition temperature: Not applicable/Not available due to the nature/properties of the product pH: 12-13 Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product Solubility: Not applicable/Not available due to the nature/properties of the product Hydrosolubility: Not applicable/Not available due to the nature/properties of the product Liposolubility: Not applicable/Not available due to the nature/properties of the product Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product Vapour pressure: Not applicable/Not available due to the nature/properties of the product Absolute density: Not applicable/Not available due to the nature/properties of the product Relative density: 1.8-2.4 Relative vapour density: Not applicable/Not available due to the nature/properties of the product Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information

Not applicable/Not available due to the nature/properties of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Unstable in contact with:

- Acids.

10.3 Possibility of hazardous reactions.

Neutralization can occur on contact with acids.

10.4 Conditions to avoid.

- Avoid contact with acids.

10.5 Incompatible materials.

Avoid the following materials:

- Acids.

10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- Corrosive vapors or gases.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness. **11.1 Information on hazard classes as defined in Regulation (EC) Nº 1272/2008.**

There are no tested data available on the product.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity;

(in accordance with Regulation (EU) 2020/878)

FIX-REPAR ANTI-OXID



Version 1Date of compilation: 16/12/2015Version 2 (replaces version 1)Revision date: 24/11/2023

Page 7 of 10 Print date: 24/11/2023

Not conclusive data for classification.

b) skin corrosion/irritation;Product classified:Skin Corrosive, Category 1: Causes severe skin burns and eye damage.

c) serious eye damage/irritation; Product classified: Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation;Product classified:Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity; Not conclusive data for classification.

f) carcinogenicity; Not conclusive data for classification.

g) reproductive toxicity; Not conclusive data for classification.

h) STOT-single exposure;Product classified:Specific target organ toxicity following a single exposure, Category 3: May cause respiratory irritation.

i) STOT-repeated exposure; Not conclusive data for classification.

j) aspiration hazard; Not conclusive data for classification.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present. No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

(in accordance with Regulation (EU) 2020/878)

FIX-REPAR ANTI-OXID



Version 1 Date of compilation: 16/12/2015

Version 2 (replaces version 1) Revision date: 24/11/2023

Page 8 of 10 Print date: 24/11/2023

12.7 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

14.1 UN number or ID number.

Transportation is not dangerous.

14.2 UN proper shipping name.

Description: ADR/RID: Not classified as hazardous for transport. IMDG: Not classified as hazardous for transport. ICAO/IATA: Not classified as hazardous for transport.

14.3 Transport hazard class(es).

Transportation is not dangerous.

14.4 Packing group.

Transportation is not dangerous.

14.5 Environmental hazards.

Transportation is not dangerous. Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): Not applicable.

14.6 Special precautions for user.

Transportation is not dangerous.

14.7 Maritime transport in bulk according to IMO instruments.

Transportation is not dangerous.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC) VOC content (p/p): 0 % VOC content: 0 g/l

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

(in accordance with Regulation (EU) 2020/878)

FIX-REPAR ANTI-OXID



Version 1 Date of compilation: 16/12/2015

Version 2 (replaces version 1) Revision date: 24/11/2023

Page 9 of 10 Print date: 24/11/2023

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.

Classification codes:

Eye Dam. 1 : Serious eye damage, Category 1 STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3 Skin Corr. 1 : Skin Corrosive, Category 1 Skin Irrit. 2 : Skin irritant, Category 2 Skin Sens. 1 : Skin sensitiser, Category 1 Skin Sens. 1B : Skin sensitiser, Category 1B

Changes regarding to the previous version:

- Change of the name of the product (SECTION 1.1).
- Change of the uses of the product (SECTION 1.2).
- Changes in the information of the supplier (SECTION 1.3).
- Change in the emergency number (SECTION 1.4).
- Change in the hazard classification (SECTION 2.1).
- Addition of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Modification of specific hazards (SECTION 2.3).
- Changes in the composition of the product (SECTION 3.2).
- Modifications in the first aid measures (SECTION 4.1).
- Modification of the symptoms (SECTION 4.2).
- Modification in the firefighting measures (SECTION 5.2).
- Modifications in the accidental release measures (SECTION 6.1).
- Modifications in the accidental release measures (SECTION 6.3).
- Modifications in the handling and storage precautions (SECTION 7.1).
- Modifications in the handling and storage precautions (SECTION 7.2).
- Change of the uses of the product (SECTION 7.3).
- Addition of exposure data (SECTION 8.1).
- Addition of personal protective equipment (SECTION 8.2).
- Modifications of the personal protective equipment (SECTION 8.2).
- Modification in the values of the physical and chemical properties (SECTION 9).
- Change in the hazard classification (SECTION 11.1).
- Addition of classification ADR/IMDG/ICAO/IATA/RID (SECTION 14).
- National legislative changes (SECTION 15.1).
- Addition of abbreviations and acronyms (SECTION 16).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

CEN: European Committee for Standardization.

PPE: Personal protection equipment.

(in accordance with Regulation (EU) 2020/878)

FIX-REPAR ANTI-OXID



Version 1 Date of compilation: 16/12/2015 Version 2 (replaces version 1) Revision date: 24/11/2023 Page 10 of 10 Print date: 24/11/2023

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/ Regulation (EU) 2020/878. Regulation (EC) No 1907/2006. Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.